

# Visu-Link VL9-S

## Resettable / Programmable Totalizer / Remote Reader for Switch / Pulse Output Meters

Firmware version 3.00 or later



### FEATURES:

- Allows a meter to be read remotely from a convenient location
- Connects to switch or electronic pulse outputs on meter register
- IP67 Certified
- “TAP” to get current meter reading / total count
- Up to 14-digits with optional decimal point
- 5 year limited warranty
- Distances to 2000 feet or more
- May be used in default mode of 6-digit reading starting at 000000 without programming
- May be reset to a reading of 000000 without going through full programming
- May be programmed to match number of digits and current reading on meter
- Accepts 1, 2, or 10 pulses per reading count increment.
- CE Certified

### PHYSICALS:

- 4.6" x 4.3" x 2" thick (11.7cm x 10.9cm x 5.1cm thick)
- Operating Temperature: -30°C to 80°C (-22°F to 176°F)
- Weight: 9oz (254g)

### METER CONNECTIVITY:

Most meters having a mechanical switch closure or open-drain / open collector low-pulsing output.

**Kemp-Meek Manufacturing, Inc.**  
101 Park Central  
Mineola, TX 75773  
Phone: 903.569.9700  
[www.kempmeek.com](http://www.kempmeek.com)

04/11/2024 Rev 2